

CLAIMS

What is claimed is:

1. A seat, comprising
a base having a front which broadens towards a rear, the
rear having a groove, and
a connector attached to the base.

2. The seat of claim 1, wherein the base comprises:
a rigid frame, and
a first layer connected to the frame.

3. The seat of claim 2, further comprising:
a second layer disposed between the first layer and the
frame.

4. The seat of claim 3, wherein:
the first layer is constructed of a resilient material, and
the second layer is constructed of a resilient material that
is denser than the first layer resilient material.

5. The seat of claim 4, wherein the groove has a dimension
matching an ischial tuberosities dimension whereby pressure is
reduced on the internal pudendal arteries.

6. The seat of claim 1, wherein the groove is beveled.

1 7. The seat of claim 3, wherein:

2 the second layer is beveled to a greater extent than the
3 frame, and

4 the first layer is beveled to a greater extent than the second
5 layer.

1 8. The seat of claim 7, wherein the groove has a dimension
2 matching an ischial tuberosities dimension whereby pressure is
3 reduced on the internal pudendal arteries.

1 9. A seat, comprising:

2 a connector;

3 a base attached to the connector, the base having a front
4 which broadens towards a rear, the rear having a groove, the
5 base further comprising:

6 a rigid frame;

7 a first layer constructed of a resilient material
8 connected to the frame, and

9 a second layer constructed of a resilient material
10 that is denser than the first layer resilient material, the second
11 layer disposed between the first layer and the frame, wherein the
12 second layer is beveled to a greater extent than the frame and the
13 first layer is beveled to a greater extent than the second layer.

1 10. A seat, comprising:

2 a base having a front which broadens towards a rear; the
3 rear having a notched groove, wherein the base further
4 comprises:

5 a rigid frame, and

6 a resilient material layer connected to the frame,
7 wherein the resilient material layer is beveled at a greater angle
8 than the frame.

1 11. The seat of claim 10, wherein the notched groove has a
2 dimension matching an ischial tuberosities dimension whereby
3 pressure is reduced on the internal pudendal arteries.

4 12. A seat, comprising:

5 a base having a front which broadens towards a rear; the
6 base having a cavity extending from near the rear towards near
7 the front of the seat.

8 13. The seat of claim 12, wherein the base comprises:

9 a rigid frame, and

10 a first layer connected to the frame.

11 14. The seat of claim 13, further comprising:

12 a second layer disposed between the first layer and the
13 frame.

14 15. The seat of claim 14, wherein:

15 the first layer is constructed of a resilient material, and

3
4

the second layer is constructed of a resilient material that
is denser than the first layer resilient material.

1

16. The seat of claim 12, wherein the cavity is beveled.

1

17. The seat of claim 14, wherein:

2

the second layer is beveled to a greater extent than the

3

frame, and

4

the first layer is beveled to a greater extent than the second

5

layer.

10
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100

18. The seat of claim 17 wherein the cavity has a dimension
matching an ischial tuberosities dimension whereby pressure is
reduced on the internal pudendal arteries.

100
99
98
97
96
95
94
93
92
91
90
89
88
87
86
85
84
83
82
81
80
79
78
77
76
75
74
73
72
71
70
69
68
67
66
65
64
63
62
61
60
59
58
57
56
55
54
53
52
51
50
49
48
47
46
45
44
43
42
41
40
39
38
37
36
35
34
33
32
31
30
29
28
27
26
25
24
23
22
21
20
19
18
17
16
15
14
13
12
11
10
9
8
7
6
5
4
3
2
1